

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier : TIRE SHINE

Product Use : Lubricant (aerosol).

Chemical Family : Mixture.

Manufacturer part no. : FTS21C

Supplier's name and address:

Radiator Specialty Co., of Canada

1711 Aimco Blvd.
Mississauga, ON, Canada
L4W 1H7

Manufacturer's name and address:

Refer to Supplier

Information Telephone # : (905) 625-9117 (Monday - Friday, 8AM - 4PM)

24 Hr. Emergency Tel # : In case of transportation emergencies: 613-996-6666 (CANUTEC)

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR).

WHMIS classification:

Class A (Pressurized containers);

Class B5 (Flammable Aerosols);

Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

Labelling: Phrases recommended to appear on a supplier label, can be found in Section 15.

WHMIS symbols required on a supplier label:



Emergency Overview : Aerosolized, clear liquid. Hydrocarbon odour.
Danger. Extremely flammable aerosol. Contents under pressure. Containers may explode if heated. May be harmful if inhaled. May cause respiratory irritation. May cause nausea, vomiting, headache and other central nervous system effects. Ingestion of large amounts may be harmful. May be an aspiration hazard. May cause eye and skin irritation.

This product contains marine pollutants.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue and unconsciousness.

Skin : May cause moderate to severe skin irritation. If product is sprayed directly on skin, symptoms of frostbite may be experienced including numbness, prickling and itching.

Eyes : May cause eye irritation. Stinging or burning sensation, redness or watering. Spraying the product directly into the eyes may cause freezing, and could cause eye damage.

Ingestion : Not an expected route of entry under normal conditions of use.
However, if the product is sprayed directly into mouth and large amounts of the liquid concentrate are swallowed, it may cause irritation to the mouth, throat and stomach. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Product may present an aspiration hazard, if ingested in large amounts, causing life-threatening lung injury.

Effects of long-term (chronic) exposure

: Prolonged skin contact may defat the skin and produce dermatitis. Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: This product contains marine pollutants. See Section 12 for more environmental information.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
n-Heptane	142-82-5	40.00 - 70.00
Petroleum gases, liquefied	68476-85-7	15.00 - 40.00

SECTION 4 - FIRST AID MEASURES

- Inhalation** : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention if symptoms persist.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Wash exposed area thoroughly with soap and water for at least 15 minutes. Seek immediate medical attention/advice.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms persist.
- Ingestion** : Do not induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Never give anything by mouth to an unconscious person. Get medical attention.
- Notes For Physician** : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

- : Extremely flammable aerosol. May be ignited by open flame. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time. Vapours are heavier than air and collect in confined and low-lying areas. Material will float on water and can be re-ignited at the water's surface.

Oxidizing properties : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

- : Aerosols are sensitive to mechanical impact. Contents under pressure. May be sensitive to static discharge.

Suitable extinguishing media : Dry chemical, foam, carbon dioxide and water fog. Do not use water jet, as this may spread burning material.

Special fire-fighting procedures/equipment

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Shield personnel to protect from venting or rupturing containers. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

- : Carbon oxides; Other unidentified organic compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Spill response/cleanup : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.

Prohibited materials : Do not use combustible absorbents, such as sawdust.

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flames. Ground all equipment during handling. Avoid contact with incompatible materials. Avoid contact with incompatible materials. Do not puncture or incinerate. Wash thoroughly after handling. Do not eat or smoke in areas of use or storage.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
- Incompatible materials** : Amines; Strong oxidizing agents.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**Exposure Limits**

<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
n-Heptane	400 ppm	500 ppm	500 ppm (2000 mg/m ³)	N/Av
Petroleum gases, liquefied	Simple Asphyxiant	N/Av	1000 ppm (1800 mg/m ³)	N/Av

Ventilation and engineering measures

- : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

- : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection

- : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers. Depending on conditions of use, an impervious apron should be worn.

Eye / face protection

- : Chemical splash goggles are recommended.

Other protective equipment

- : An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

- : Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink, smoke or use cosmetics while working with this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|---|--|---|--|
| Physical state | : Liquid aerosol. | Appearance | : Aerosolized, clear liquid. |
| Odour | : Hydrocarbon odour. | Odour threshold | : N/Av |
| pH | : N/Av | | |
| Boiling point | : - 26.7°C (- 16°F)
(propellant)
93.3°C (200°F)
(concentrate) | Specific gravity | : 0.7 (concentrate)
0.54 (propellant) |
| Melting/Freezing point | : N/Av | Coefficient of water/oil distribution | : N/Av |
| Vapour pressure (mmHg @ 20° C / 68° F) | : N/Av | Solubility in water | : slightly soluble |
| Vapour density (Air = 1) | : > 1 | Evaporation rate (n-Butyl acetate = 1) | : > 1 |
| Volatile organic Compounds (VOC's) | : N/Av | Volatiles (% by weight) | : 90% |
| Flash point | : - 104.4°C (- 156°F) (propellant) | | |
| Flash point Method | : N/Av | Auto-ignition temperature | : N/Av |

Lower flammable limit (% by vol.)	: 2.0 (propellant)	Upper flammable limit (% by vol.)	: 10.0 (propellant)
Flame Projection Length	: 76 cm (29.9")	Flashback observed	: YES
Absolute pressure of container	: N/Av	Viscosity	: N/Av
General Information	: No additional information.		

Section 10: STABILITY AND REACTIVITY

Stability and reactivity	: Stable under the recommended storage and handling conditions prescribed.
Hazardous polymerization	: Hazardous polymerization does not occur.
Conditions to avoid	: Avoid heat and open flame. Extremes of temperature and direct sunlight. Ensure adequate ventilation, especially in confined areas.
Materials To Avoid And Incompatibility	: Amines; Strong oxidizing agents
Hazardous decomposition products	: None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs	: Eyes, skin, respiratory system, digestive system, central nervous system.
Routes of exposure	: <i>Inhalation:</i> YES <i>Skin Absorption:</i> NO <i>Skin & Eyes:</i> YES <i>Ingestion:</i> YES
Irritancy	: May cause moderate to severe skin irritation. May cause eye irritation.
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC₅₀ (4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
n-Heptane	25 000 ppm (102.5 mg/L) (vapour)	> 15 000 mg/kg	> 2000 mg/kg (No mortality)
Petroleum gases, liquefied	276 000 ppm (Butane)	N/Av (gas)	N/Av (gas)

Carcinogenic status	: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
Reproductive effects	: Not expected to have other reproductive effects.
Teratogenicity	: Not expected to be a teratogen.
Mutagenicity	: Not expected to be mutagenic in humans.
Epidemiology	: None known or reported by the manufacturer.
Sensitization to material	: Not expected to be a skin or respiratory sensitizer.
Synergistic materials	: None known or reported by the manufacturer.
other important hazards	: CNS depression may result from extreme exposures.
Conditions aggravated by overexposure	: Pre-existing eye, skin, respiratory, liver, kidney and central nervous system disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	: The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. This product contains marine pollutants. The product contains the following substances which are hazardous for the environment: Heptane.
--------------------	--

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
n-Heptane	142-82-5	5.738 mg/L (Rainbow trout)	1.284 mg/L/28-day (Rainbow trout)	None.
Petroleum gases, liquefied	68476-85-7	N/Av	N/Av	N/Av

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
n-Heptane	142-82-5	0.2 mg/L Chaetogammarus marinus (Water flea)	0.06 - 0.23 mg/L	1
Petroleum gases, liquefied	68476-85-7	N/Ap	N/Ap	N/Ap

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
n-Heptane	142-82-5	4.338 mg/L/72hr (Green algae)	0.97 mg/L/72hr	None.
Petroleum gases, liquefied	68476-85-7	N/Ap	N/Ap	N/Ap

- Mobility** : No data is available on the product itself.
- Persistence** : No data is available on the product itself. Contains: Heptane. Heptane is considered to be readily biodegradable.
- Bioaccumulation potential** : No data is available on the product itself. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
n-Heptane (CAS 142-82-5)	4.66	2000
Petroleum gases, liquefied (CAS 68476-85-7)	2.89 (Butane)	33 (Butane)


Other Adverse Environmental effects

- : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Do not puncture or incinerate containers.
- Methods of Disposal** : Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	None	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDGR, refer to Section 1.17 for additional exemption information, if shipping under this exemption.				

SECTION 15 - REGULATORY INFORMATION**Labelling:**

Danger. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. May be harmful if inhaled. May cause nausea, vomiting, headache and other central nervous system effects. May cause respiratory irritation. Ingestion of large amounts may be harmful. May be an aspiration hazard. May cause eye and skin irritation.

Precautions: Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flames. Ground all equipment during handling. Avoid contact with incompatible materials. Do not puncture or incinerate containers. Wash thoroughly after handling. Do not eat or smoke in areas of use or storage. Store in a cool, dry, well ventilated area, away from heat and ignition sources.

FIRST AID: If inhaled, move to fresh air. If breathing stops, provide artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention if symptoms persist. For skin contact, immediately remove contaminated clothing then wash thoroughly with soap and water for at least 15 minutes. Seek immediate medical attention/advice. For eye contact, flush with running water for at least 15 minutes. Get medical attention if symptoms persist. If ingested, do not induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Never give anything by mouth to an unconscious person. Get medical attention if symptoms persist.

Refer To Material Safety Data Sheet for further information.

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.


SECTION 16 - OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Services
CNS: Central Nervous System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
LC: Lethal Concentration
LD: Lethal Dose
MSHA: Mine Safety and Health Administration
N/Ap: Not Applicable
N/Av: Not Available
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
RTECS: Registry of Toxic Effects of Chemical Substances
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2017.
2. International Agency for Research on Cancer Monographs, searched 2017.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2017 (Chempendium, HSDB and RTECs).
4. Material Safety Data Sheets from manufacturer.
5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2017.

<p><u>Prepared for:</u> Radiator Specialty Co. of Canada 1711 Aimco Blvd. Mississauga, ON, Canada, L4W 1H7 Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

MSDS Preparation Date (mm/dd/yyyy)

: 07/31/2007

MSDS Revision Date (mm/dd/yyyy)

: 10/26/2017

Revision No.

: 5

Revision Information

: (M)SDS sections updated:
 12. ECOLOGICAL INFORMATION

END OF DOCUMENT