

# Safety Data Sheet

Issue Date: 06-Jun-2016

Revision Date: 09-Jun-2016

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Black Vulcanizing Cement - Brush Flammable  
Black Vulcanizing Cement - Brush Extra Thick Flammable

### Other means of identification

**SDS #** ELG-003

**Product Code** Catalog Numbers: 1-782, 1-783, 1-781, 1-784, 1-785, 2-782, 2-783, 2-781, 2-784, 2-785, 4-782, 4-783, 4-781, 4-784, 4-785

**UN/ID No** UN1133

### Recommended use of the chemical and restrictions on use

**Recommended Use** Rubber adhesive.

### Details of the supplier of the safety data sheet

**Supplier Address**  
ELGI Rubber Company, LLC  
600 N. Magnolia Ave.  
Luling, TX 78648  
Ph: 830-875-5539

### Emergency Telephone Number

**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Black, high viscosity liquid      **Physical state** Liquid      **Odor** Petrollic

### Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

### Signal Word

**Danger**

### Hazard statements

Causes skin irritation  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor



**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do not induce vomiting  
IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other hazards**

Very toxic to aquatic life with long lasting effects

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%
N-Heptane	142-82-5	85-95
Carbon Black	1333-86-4	0-5

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST-AID MEASURES

### First Aid Measures

<b>General Advice</b>	Provide this SDS to medical personnel for treatment.
<b>Eye Contact</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin Contact</b>	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If symptoms persist, call a physician.
<b>Ingestion</b>	Do not induce vomiting. Immediately call a poison center or doctor/physician.

### Most important symptoms and effects

<b>Symptoms</b>	Causes skin irritation. May be harmful in contact with skin. May cause pulmonary edema. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness, headache, nausea, and loss of coordination.
-----------------	---

### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.
---------------------------	--

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media** Do not use solid water streams.

### Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

**Hazardous Combustion Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

### Explosion Data

**Sensitivity to Static Discharge** Take precautionary measures against static discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions**                      Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing vapors or mists.

### Environmental precautions

**Environmental precautions**            Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

### Methods and material for containment and cleaning up

**Methods for Containment**                Prevent further leakage or spillage if safe to do so. Prevent evaporation by covering with foam. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

**Methods for Clean-Up**                    Use only non-sparking tools. Place in properly labeled, sealed, non-leaking containers. Dispose of contents/container via a licensed waste disposal contractor. For waste disposal, see section 13 of the SDS.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on Safe Handling**                Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep cool.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions**                      Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat sensitive-store under inert gas.

**Incompatible Materials**                Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m <sup>3</sup>	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>
Carbon Black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

**Appropriate engineering controls**

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Showers  
 Eyewash stations  
 Ventilation systems. Explosion-proof general and local exhaust ventilation.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.

**Skin and Body Protection** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

**Respiratory Protection** If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	Petrolic
<b>Appearance</b>	Black, high viscosity liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	Not determined	
<b>Melting Point/Freezing Point</b>	-90.0 to -90.1 °C / -131.7 to -130.3 °F	
<b>Boiling Point/Boiling Range</b>	98.1 to 98.7 °C 208.5 to 209.6 °F	
<b>Flash Point</b>	-4.0 °C / 24.8 °F	
<b>Evaporation Rate</b>	4	(butyl acetate = 1)
<b>Flammability (Solid, Gas)</b>	Not determined	
<b>Flammability Limits in Air</b>		Not applicable
<b>Upper Flammability Limits</b>	7%	
<b>Lower Flammability Limit</b>	1.1%	
<b>Vapor Pressure</b>	110.7 hPa (83.0 mmHg) at 37.7 °C (99.9°F) , 53.3 hPa (40.0 mmHg) at 20.0 °C (68.0°F)	
<b>Vapor Density</b>	3.30	(Air=1)
<b>Relative Density</b>	0.684 g/mL at 25°C (77°F)	
<b>Water Solubility</b>	Not determined	
<b>Solubility in other solvents</b>	Insoluble	
<b>Partition Coefficient</b>	log Pow > 3.000	
<b>Auto-ignition Temperature</b>	223.0 °C / 433.4 °F	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	

**Other Information**

Molecular weight 100.2 g/mol  
VOC Content (%) N/A

**10. STABILITY AND REACTIVITY**

**Reactivity**

Not reactive under normal conditions.

**Chemical Stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to Avoid**

Heat, flames and sparks.

**Incompatible Materials**

Strong oxidizing agents.

**Hazardous Decomposition Products**

None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

**Eye Contact** Avoid contact with eyes.

**Skin Contact** Causes skin irritation. May be harmful in contact with skin.

**Inhalation** May cause drowsiness or dizziness. May cause irritation to the mucous membranes and upper respiratory tract.

**Ingestion** May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

**Component Information**

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
N-Heptane 142-82-5	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> ( Rat ) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-

**Information on physical, chemical and toxicological effects**

**Symptoms** Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Carcinogenicity** Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon Black 1333-86-4	A3	Group 2B		X

**Legend**

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A3 - Animal Carcinogen  
 IARC (International Agency for Research on Cancer)  
 Group 2B - Possibly Carcinogenic to Humans  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**STOT - single exposure** May cause drowsiness or dizziness.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 3,000.00 mg/kg  
 ATEmix (inhalation-dust/mist) 108.00 mg/L

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
N-Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
N-Heptane 142-82-5	4.66

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**                      Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

**Contaminated Packaging**              Disposal should be in accordance with applicable regional, national and local laws and regulations.

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
N-Heptane 142-82-5	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**Note**    Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

**UN/ID No**                                      UN1133  
**Hazard Class**                                3  
**Packing Group**                              II

**IATA**

**UN/ID No**                                      UN1133  
**Hazard Class**                                3  
**Packing Group**                              II

**IMDG**

**UN/ID No**                                      UN1133  
**Hazard Class**                                3  
**Packing Group**                              II  
**Marine Pollutant**                            Yes

**15. REGULATORY INFORMATION**

**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
N-Heptane	X	X	X	Present	X	Present	X	X
Carbon Black	X	X	X	Present	X	Present	X	X

**Legend:**

- TSCA* - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL* - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS* - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS* - Japan Existing and New Chemical Substances
- IECSC* - China Inventory of Existing Chemical Substances
- KECL* - Korean Existing and Evaluated Chemical Substances
- PICCS* - Philippines Inventory of Chemicals and Chemical Substances
- AICS* - Australian Inventory of Chemical Substances



**US Federal Regulations**

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
N-Heptane 142-82-5	X	X	X
Carbon Black 1333-86-4	X	X	X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	3	0	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical hazards</b>	<b>Personal Protection</b>
	1	3	0	Not determined

Issue Date: 06-Jun-2016  
 Revision Date: 09-Jun-2016  
 Revision Note: New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**