

Safety Data Sheet

Issue Date: 06-Jun-2016

Revision Date: 09-Jun-2016

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Black Vulcanizing Cement - Spray Flammable

Other means of identification

SDS # ELG-002

Product Code Catalog Numbers: 1-711, 1-786, 1-787, 2-711, 2-786, 2-787, 4-711, 4-786, 4-787

UN/ID No UN1133

Recommended use of the chemical and restrictions on use

Recommended Use Rubber adhesive.

Details of the supplier of the safety data sheet

Supplier Address

ELGI Rubber Company, LLC
600 N. Magnolia Ave.
Luling, TX 78648
Ph: 830-875-5539

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black, high viscosity liquid

Physical state Liquid

Odor Petrolic

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard statements

Causes skin irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 If skin irritation occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting
 IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
N-Heptane	142-82-5	85-95
Carbon Black	1333-86-4	0-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

- General Advice** Provide this SDS to medical personnel for treatment.

- Eye Contact** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

- Skin Contact** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

- Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

- Ingestion** Do not induce vomiting. Immediately call a poison center or doctor/physician.

Most important symptoms and effects

Symptoms	Causes skin irritation. May be harmful in contact with skin. May cause pulmonary edema. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness, headache, nausea, and loss of coordination.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.
---------------------------	--

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media Do not use solid water streams.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂).

Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing vapors or mists.
-----------------------------	---

Environmental precautions

Environmental precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so. Prevent evaporation by covering with foam. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.
Methods for Clean-Up	Use only non-sparking tools. Place in properly labeled, sealed, non-leaking containers. Dispose of contents/container via a licensed waste disposal contractor. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat sensitive-store under inert gas.

Incompatible Materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Showers
Eyewash stations
Ventilation systems. Explosion-proof general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Petrolic
Appearance	Black, high viscosity liquid	Odor Threshold	Not determined
Color	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	-90.0 to -90.1 °C / -131.7 to -130.3 °F	
Boiling Point/Boiling Range	98.1 to 98.7 °C 208.5 to 209.6 °F	
Flash Point	-4.0 °C / 24.8 °F	
Evaporation Rate	4	(butyl acetate = 1)
Flammability (Solid, Gas)	Not determined	
Flammability Limits in Air		Not applicable
Upper Flammability Limits	7%	
Lower Flammability Limit	1.1%	
Vapor Pressure	110.7 hPa (83.0 mmHg) at 37.7 °C (99.9°F), 53.3 hPa (40.0 mmHg) at 20.0 °C (68.0°F)	
Vapor Density	3.30	(Air=1)
Relative Density	0.684 g/mL at 25°C (77°F)	
Water Solubility	Not determined	
Solubility in other solvents	Insoluble	
Partition Coefficient	log Pow > 3.000	
Auto-ignition Temperature	223.0 °C / 433.4 °F	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

Other Information

Molecular weight	100.2 g/mol
VOC Content (%)	N/A

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

- Eye Contact** Avoid contact with eyes.
- Skin Contact** Causes skin irritation. May be harmful in contact with skin.
- Inhalation** May cause drowsiness or dizziness. May cause irritation to the mucous membranes and upper respiratory tract.
- Ingestion** May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon Black 1333-86-4	A3	Group 2B		X

Legend

- ACGIH (American Conference of Governmental Industrial Hygienists)*
- A3 - Animal Carcinogen*
- IARC (International Agency for Research on Cancer)*
- Group 2B - Possibly Carcinogenic to Humans*
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)*
- X - Present*

STOT - single exposure May cause drowsiness or dizziness.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

- ATEmix (dermal)** 3,000.00 mg/kg
- ATEmix (inhalation-dust/mist)** 108.00 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
N-Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
N-Heptane 142-82-5	4.66

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
N-Heptane 142-82-5	Toxic Ignitable

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1133
Proper Shipping Name	Adhesives
Hazard Class	3
Packing Group	II

IATA

UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II

IMDG

UN/ID No UN1133
Proper Shipping Name Adhesives
Hazard Class 3
Packing Group II
Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
N-Heptane	X	X	X	Present	X	Present	X	X
Carbon Black	X	X	X	Present	X	Present	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
N-Heptane 142-82-5	X	X	X
Carbon Black 1333-86-4	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	3	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	1	3	0	Not determined

Issue Date: 06-Jun-2016
 Revision Date: 09-Jun-2016
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet