



# Safety Data Sheet

REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Vulcanizing Compound A

**Chemical Family:** Aliphatic Hydrocarbons

**Product Use:** Adhesive / Filler Rubber

**Restrictions on Use:** Use as directed by manufacturer

**Manufacturer:** Rema Tip Top - North America  
240 Pegasus Ave. 2<sup>nd</sup> Floor  
Northvale, NJ 07647  
Phone: 201 256-8200

**24-Hour Emergency Phone Number:** North America: 800-424-9300 (CHEMTREC)  
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

## 2. HAZARD IDENTIFICATION

### GHS Classifications

#### **Health Hazards**

Skin Irritation, Category 2

Eye Irritation, Category 2B

Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Central Nervous System, Inhalation, Ingestion, Skin absorption

Aspiration Hazard, Category 1

#### **Physical Hazards**

Flammable Liquid, Category 2

#### **Environmental Hazards**

Chronic Aquatic Toxicity, Category 2

### **GHS-Labeling Pictograms:**



**Signal Word: Danger!**



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

---

### Hazard Statements

H225: Highly flammable liquid and vapor  
H304: May be fatal if swallowed and enters airways  
H315: Causes skin irritation  
H320: Causes eye irritation  
H336: May cause drowsiness or dizziness  
H411: Toxic to aquatic life with long lasting effects

### Precautionary Statements

#### Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P233: Keep container tightly closed.  
P235: Keep cool.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing vapors.  
P264: Wash skin and exposed areas thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection.

#### Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.  
P303 + P361 + P353: IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331: Do NOT induce vomiting.  
P332 + P313: If skin irritation occurs: Get medical advice/attention.  
P337 + P313: If eye irritation persists: Get medical advice/attention.  
P362: Take off contaminated clothing and wash before reuse.  
P370 + P378: In case of fire: Use dry chemical, carbon dioxide, fog, or water spray for extinction.  
P391: Collect spillage.

#### Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405: Store locked up.

#### Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### Chemical characterization

Aliphatic Hydrocarbons

Component*	CAS #	% By Wt.
Naphtha, petroleum, hydrotreated	64742-49-0	25 – 35
Zinc Oxide	1314-13-2	< 3

\*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

### 4. FIRST AID MEASURES

#### Inhalation

**Symptoms & Effects:** Irritation of the nose and airways, central nervous system depression, nausea, dizziness, drowsiness, weakness, fatigue, headache, lack of coordination, coma

**Measures:** Immediately remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, begin artificial respiration. If breathing is difficult, administer oxygen. Seek immediate medical attention.

#### Skin Contact

**Symptoms & Effects:** Skin irritation, redness, burning, drying, cracking of the skin, dermatitis

**Measures:** Immediately wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes while washing. Wash contaminated clothing before reuse. If skin irritation persists, seek medical attention.

#### Eye Contact

**Symptoms & Effects:** Eye irritation, stinging, tearing, redness, swelling of the eyes

**Measures:** Immediately rinse eyes with water for at least 15 minutes. Remove contact lenses after the initial few minutes and if easy to do so and resume rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while rinsing. If eye irritation persists, seek medical attention.

#### Ingestion

**Symptoms & Effects:** Stomach or intestinal irritation, nausea, irritation of the throat, central nervous system depression, dizziness, drowsiness, weakness, fatigue, and headache. Swallowing large amounts may cause for material to enter the lungs during swallowing or vomiting, leading to lung inflammation and other lung damages.

**Measures:** Seek immediate medical attention. Do NOT induce vomiting as this material is an aspiration hazard. If the victim is drowsy or unconscious, do not give anything by mouth. If victim is conscious, give at least 3-4 glasses of water. Place individual on their left side and place their head down. Do not leave victim unattended.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

---

### 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Carbon dioxide, Dry chemical, Foam, Water spray

**Unsuitable Extinguishing Media:** Water jet/stream (See precautions)

**Hazardous Combustion Products:** Nitrogen oxides, Sulfur oxides, Carbon monoxide, Carbon dioxide

**Protective Equipment for Fire-Fighters:** Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Precautions for Fire-Fighters:** Highly flammable liquid. Vapors are heavier than air and may travel along the ground to some distance source of ignition and cause a flashback fire danger. Direct water stream or water jets may create an additional fire hazard. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop a leak. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Full-face, self-contained breathing apparatus should be worn at all times. Use water spray to cool fire exposed surfaces and to protect personnel.

### 6. ACCIDENTAL RELEASE MEASURES

**Protective Equipment:** Recommended to wear chemical splash goggles & resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

**Personal Precautions:** Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

**Environmental Precautions:** Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike or using oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Methods & Materials for Clean-Up:** Immediately evacuate the spilled area and provide maximum ventilation. Only personnel equipped with proper eye, and skin protection should be permitted in the area. Eliminate all ignition sources from the area. All equipment used when handling the product must be grounded. Use clean, non-sparking tools to collect absorbed material. Construct a dike to contain spill. Contain spilled material with inert, non-combustible absorbent materials such as sand, earth, diatomaceous earth, or vermiculite. After all visible traces have been removed, thoroughly wet vacuum the area. Do not allow spilled material to enter public drainage system or open water courses. Transfer to a suitable container for disposal according to proper federal, state, and local regulations. Notify the proper response units and agencies for any uncontained releases or spills.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

### 7. HANDLING AND STORAGE

**Handling:** Containers of this material may be hazardous when emptied. Since emptied containers still contain product residues (vapor, liquid, or solid), all hazard precautions given in this SDS must be observed. Prevent exposure to ignition sources. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not cut, drill, grind, weld or perform similar operations on or near containers.

Avoid breathing vapors or mists of this product. Use product with adequate ventilation. Avoid eye and skin contact with this material. Skin and eye PPE should be worn at all times when handling this product. When adequate ventilation is not provided, respiratory PPE should also be used. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Do not eat, drink or smoke when using this product.

**Storage:** Store in a cool, dry, ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up. Keep away from food, drink, and animal foodstuffs.

**Incompatible Materials:** Oxidizing agents

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Exposure Limits :

Exposure limits have not been established for this product.

<b>Naphtha, petroleum</b>	<b>CAS # 64742-49-0</b>	
ACGIH	Time Weighted Average (TWA)	
n-hexane <1%)		50 ppm
Alkanes C-7		400 ppm;

<b>Zinc Oxide</b>	<b>CAS # 1314-13-2</b>	
OSHA	Permissible Exposure Limit (PEL)	5 mg/m <sup>3R</sup>
ACGIH	TWA/STEL	2/10 mg/m <sup>3</sup>
NIOSH	Recommended Exposure Limit (REL)	5 mg/m <sup>3</sup>

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. Provide readily accessible eye wash stations and safety showers.

**Occupational Exposure Controls:** Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Protective and Hygiene measures:** Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

**Eye Protection:** Recommended to wear tight fitting, chemical splash goggles when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

**Hand Protection:** Recommended to wear suitable resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Suitable gloves will be based on product use and the period of use.

**Skin Protection:** Recommended to wear long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

**Respiratory Protection:** A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Black Paste

**Odor:** Hydrocarbon-like

**Odor Threshold:** No data available

**pH:** No data available

**Melting/Freezing point:** < -4°F (< -20°C)

**Boiling Point/ Range:** 145 – 212°F (63 – 100°C)

**Flash point (Tag closed cup):** -13°F (-25°C)

**Evaporation rate:** No data available

**Flammability: Lower Limit:** 1.1% (V) **Upper Limit:** 7.4% (V)

**Vapor pressure:** 245 hPa @ 68°F (20°C)

**Relative vapor density:** > 1 (Air = 1)

**Density:** 1.01 g/cm<sup>3</sup> (8.42 lbs/gal) @ 68°F (20°C)

**Solubility in water:** Insoluble

**Partition coefficient (n-octanol/water):** No data available

**Auto-ignition temperature:** 500°F (260°C)

**Ignition temperature:** No data available



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

**Decomposition temperature:** No data available

**Viscosity (dynamic):** No data available

### 10. STABILITY AND REACTIVITY

**Reactivity:** No decomposition if stored and applied as directed.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Product will not undergo hazardous polymerization or other hazardous reactions if storage and use directions are followed.

**Conditions to Avoid:** Heat, Sparks, Open flames, Other ignition sources

**Incompatible Materials:** Oxidizing agents

**Hazardous decomposition products:** Nitrogen oxides, Sulfur oxides, Carbon monoxide, Carbon dioxide

### 11. TOXICOLOGICAL INFORMATION

**Primary Routes of Exposure:** Inhalation, Skin contact, Eye contact, Ingestion

**Symptoms Related to Physical, Chemical and Toxicological Characteristics:** Irritation of the nose and airways, central nervous system depression, nausea, dizziness, drowsiness, weakness, fatigue, headache, lack of coordination, coma, skin irritation, redness, burning, drying, cracking of the skin, dermatitis, eye irritation, stinging, tearing, redness, swelling of the eyes, and stomach or intestinal irritation. Swallowing large amounts may cause for material to enter the lungs during swallowing or vomiting, leading to lung inflammation and other lung damages.

**Delayed and Immediate Effects & Chronic Effects from Exposure:** This product may result in central nervous system depression, with symptoms such as nausea, dizziness and drowsiness. This substance is not a suspected carcinogen as outlined by OSHA, IARC, ACGIH and the NTP (see below).

#### **Measures of Toxicity:**

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: LD<sub>50</sub> Rat: > 5,400 mg/kg

Acute Dermal Toxicity: LD<sub>50</sub> Rabbit: No sufficient data available

Acute Inhalation Toxicity: LC<sub>50</sub> Rat: No sufficient data available

#### **Naphtha, petroleum**

Acute Oral Toxicity

Acute Dermal Toxicity

#### **Zinc Oxide**

**CAS # 64742-49-0**

LD<sub>50</sub> Rat: > 15,000 mg/kg

LD<sub>50</sub> Rabbit: > 3,000 mg/kg

**CAS # 1314-13-2**



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

Acute Oral Toxicity LD<sub>50</sub> Mouse: 7,950 mg/kg  
Acute Inhalation Toxicity LC<sub>50</sub> Mouse: 2,500 mg/m<sup>3</sup>

### Carcinogen Claims:

OSHA: **None**, International Agency for Research on Cancer (IARC): **None**

ACGIH: **None**, National Toxicology Program (NTP) Report on Carcinogens: **None**

## 12. ECOLOGICAL INFORMATION

**Eco-toxicity:** This substance is toxic to aquatic organisms with long lasting effects. It is strongly advised that this substance does not enter the environment. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Zinc Oxide** CAS # 1314-13-2  
Toxicity to Fish LC<sub>50</sub> – 1.1 mg/l (Rainbow Trout; 96 h)  
Toxicity to Daphnia EC<sub>50</sub> – 0.098 mg/l (Water flea; 48 h)

**Persistence & Degradability:** No data available

**Bio-accumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** No data available

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.  
Contaminated packaging should be emptied as far as possible before disposal.

## 14. TRANSPORT INFORMATION

### DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1133

PROPER SHIPPING NAME: Adhesives, containing a flammable liquid

TRANSPORTATION HAZARD CLASS: 3

PACKING GROUP: II

HAZARD LABEL: Flammable Liquid

### IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 3

UN NUMBER: UN1133

MARINE POLLUTANT: Yes

EmS: F-E; S-D

IMDG PACKING GROUP: II

HAZARD LABEL: Flammable Liquid





# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

### Description of the goods

ADHESIVES containing flammable liquid

### IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 3

UN NUMBER: UN1133

HAZARD LABEL: Flammable Liquid

### Description of the goods

Adhesives, containing flammable liquid

## 15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

### SARA Title III

#### Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37, *None*

#### Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37, *None*

### OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements.

Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

### CANADIAN REGULATIONS

WHMIS Classification: Same as OSHA GHS Classification

### STATE REGULATIONS

#### California Proposition 65

This product does not contain chemicals known to the state of California to cause cancer, birth defects, or reproductive harm.

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List/Permissible Exposure List

California Toxic air contaminants

Connecticut Permissible Exposure Limits

Delaware List of Chemicals and RQs



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

---

Hawaii Permissible Exposure Limits  
Idaho Toxic Air Pollutants  
Illinois Toxic Air Contaminants List  
Louisiana Toxic Air Pollutants  
Maine Hazardous Air Pollutants  
Maryland Toxic Air Pollutants for Existing Sources  
Massachusetts Hazardous Substances List  
Michigan Permissible Exposure Limits  
Minnesota Hazardous Substances  
Minnesota Permissible Exposure Limits  
Nebraska Hazardous Air Pollutants  
New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List  
New York List of Hazardous Substances  
Ohio Toxic Air Contaminants  
Oklahoma Toxic Air Contaminants  
North Carolina TAP Emissions Rates Requiring a Permit  
Pennsylvania Hazardous Substances List  
Rhode Island Toxic Air Contaminants  
Tennessee Permissible Exposure Limits  
Vermont Hazardous Air Contaminants/Permissible Exposure Limits  
Washington Permissible Exposure Limits for Airborne Contaminants.  
West Virginia Toxic Air Pollutant List  
Wisconsin hazardous Air Contaminants

**Note:** Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.



# Safety Data Sheet

## REMA Tire Repair Materials

Product #: 50F & 51F Compound A

SDS #: RTT-TRM-050

Rev. # 5

Rev. Date: 1/23/2017

### 16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

**MEDICAL EMERGENCIES:**

Call CHEMTREC 24 hours a  
Day for emergency information  
800-424-9300

**FOR ANY OTHER INFORMATION:**

REMA TIP TOP - NORTH AMERICA  
240 Pegasus Ave. 2<sup>nd</sup> Floor  
NORTHVALE, NJ 07647  
201-256-8200

**NOTICE:** REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

**NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.**